

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305



Revision: 26.05.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier** 600102
- **Trade name:** Moisture proofing spray E-COLL
- **Article number:** 4317784006644
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Anti-moisture agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH  
EDE Platz 1  
D-42389 Wuppertal  
Germany  
  
Tel. +49 202 6096-0  
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**  
  
GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 1)

hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes, &lt; 5% n-hexane

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

EUH018 In use may form flammable/explosive vapour-air mixture.

Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards**
**· Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

**\* SECTION 3: Composition/information on ingredients**
**· 3.2 Chemical characterisation: Mixtures**

 · **Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

EC number: 929-018-5	Hydrocarbons, C10-C13, n-alkanes, <2% aromatics ⚠ Asp. Tox. 1, H304	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure ⚠ Flam. Gas 1, H220 Press. Gas (Comp.), H280	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220 ⚠ Acute Tox. 1, H330 Press. Gas (Comp.), H280	10-<25%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 2)

CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1 Reg.nr.: 01-2119475514-35-XXXX	hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes, < 5% n-hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	2.5-10%
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-0000	2-(2-butoxyethoxy)ethanol Eye Irrit. 2, H319	0-<2.5%
CAS: 57855-77-3 EINECS: 260-991-2	Naphthalenesulfonicacid, dinonyl-, calciumsalt Skin Irrit. 2, H315; Eye Irrit. 2, H319	0-<2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Personal protection for the First Aider.  
Take affected persons out of danger area and lay down.

**After inhalation:**

Supply fresh air.  
Seek medical treatment in case of complaints.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**

Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; call for medical help immediately.  
Drink plenty of water and provide fresh air. Call for a doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

---

**Trade name: Moisture proofing spray E-COLL**

---

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.  
Can form explosive gas-air mixtures.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

---

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

---

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas.
- **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.  
Do not spray onto a naked flame or any incandescent material.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 4)

Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**CAS: 112-34-5 2-(2-butoxyethoxy)ethanol**

IOELV	Short-term value: 101.2 mg/m <sup>3</sup> , 15 ppm
	Long-term value: 67.5 mg/m <sup>3</sup> , 10 ppm

- **DNELs**

**CAS: 112-34-5 2-(2-butoxyethoxy)ethanol**

Oral	DNEL (population)	1.25 mg/kg bw/day (cus)
Dermal	DNEL (worker)	20 mg/kg bw/day (professional use)
	DNEL (population)	10 mg/kg bw/day (cus)
Inhalative	Long term value for employees	34 mg/m <sup>3</sup> (cus)
		67.5 mg/m <sup>3</sup> (professional use)
	DNEL (worker)	67.5 mg/m <sup>3</sup> (professional use)
	DNEL (population)	34 mg/m <sup>3</sup> (cus)

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes and skin.

- **Respiratory protection:**

Respiratory protection is not required when used properly and under normal conditions.  
 Use breathing protection if ventilation is inadequate  
 Filter A2  
 Short term filter device:  
 Filter A/P2

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 5)

**· Protection of hands:**

Protective gloves

**· Material of gloves**

Penetration time (min.) : &gt; 6h

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:** Safety glasses**· Body protection:** Light weight protective clothing**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:****Form:**

Aerosol

**Colour:**

Yellowish

**· Odour:**

Characteristic

**· Odour threshold:**

Not determined.

**· pH-value:**

Not determined.

**· Change in condition****Melting point/freezing point:**

Undetermined.

**Initial boiling point and boiling range:** Not applicable, as aerosol.**· Flash point:**

Not applicable, as aerosol.

**· Flammability (solid, gas):**

Not applicable.

**· Decomposition temperature:**

Not determined.

**· Auto-ignition temperature:**

Product is not selfigniting.

**· Explosive properties:**

Not determined.

**· Explosion limits:****Lower:**

Not determined.

**Upper:**

Not determined.

**· Oxidising properties**

Not determined.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 6)

- **Vapour pressure at 20 °C:** 4,200 hPa
- **Density at 20 °C:** 0.7 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
  - Organic solvents:** > 90 %
- **9.2 Other information** No further relevant information available.

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****CAS: 106-97-8 butane, pure**

Inhalative LC50/4h 658 ppm (rat)

**CAS: 74-98-6 propane**Inhalative LC50/4h >20 mg/m<sup>3</sup> (rat)**CAS: 64742-49-0 hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cycloalkanes, < 5% n-hexane**

Oral LD50 &gt;5,000 mg/kg (rat)

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 7)

Dermal	LD50	>2,920 mg/kg (rat) >2,000 mg/kg (rabbit)
Inhalative	LC50/4h	>25 mg/m <sup>3</sup> (rat)
<b>CAS: 112-34-5 2-(2-butoxyethoxy)ethanol</b>		
Oral	LD50	4,900 mg/kg (rat)
Dermal	LD50	4,900 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****CAS: 112-34-5 2-(2-butoxyethoxy)ethanol**

LC50 akut (96h)	1,300 mg/L (Lepomis macrochirus)
LC50 akut	>100 mg/L (Brachydanio rerio)
LC50	>100 mg/L (crustacean)
EC50	>100 mg/l (Desmodesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**  
Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods:**  
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.  
Observe local regulations.

**European waste catalogue**

16 05 05 | gases in pressure containers other than those mentioned in 16 05 04

**SECTION 14: Transport information**

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG, IATA** AEROSOLS
- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2 Gases.
- **Label** 2.1

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 9)

· <b>14.4 Packing group</b>	
· <b>ADR, IMDG</b>	Void
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Warning: Gases.
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN1950, AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I Methanol**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.05.2020

Version number 305

Revision: 26.05.2020

**Trade name: Moisture proofing spray E-COLL**

(Contd. of page 10)

**· Exposure scenario(s)**

Exposure scenario(s) of ingredients (if present) are available on request at:  
sdb@ede.de

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**· Department issuing SDS:** Product safety department**· Contact:**

Head of Product Safety Department  
sdb@ede.de

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1: Flammable gases – Category 1  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 2: Flammable liquids – Category 2  
Acute Tox. 1: Acute toxicity - inhalation – Category 1  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**· \* Data compared to the previous version altered.**