

Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600105

· Trade name: Zinc dust paint E-COLL

· Article number: 4317784349178

· UFI: GCWX-CQJE-W90V-5TYG

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Coating material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS0

· Signal word Warning

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom. quicklime

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	25-50%
	(Cont	d on nogo 2)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	(Contd. of page 2 10-<25%
EC number: 918-668-5	♠ Flam. Liq. 3, H226	. – –
Index number: 649-356-00-4	Asp. Tox. 1, H304	
Reg.nr.: 01-2119455851-35-xxxx	Aquatic Chronic 2, H411	
01-2119487492-29-XXXX	₹ STOT SE 3, H335-H336	
CAS: 1330-20-7	xylene	2.5-10%
EINECS: 215-535-7	Flam. Liq. 3, H226	
Index number: 601-022-00-9	Asp. Tox. 1, H304	
Reg.nr.: 01-2119488216-32-xxxx	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 1314-13-2	zinc oxide	2.5-10%
EINECS: 215-222-5	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Index number: 030-013-00-7		
Reg.nr.: 01-2119463881-32		
CAS: 1305-78-8	quicklime	<1.25%
EINECS: 215-138-9	♦ Eye Dam. 1, H318	
Reg.nr.: 01-2119475325-36-XXXX		
01-2119666323-39-XXXX		
01-2119862019-36-XXXX		
01-2119976279-19-XXXX		
01-2120034600-72-XXXX		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; call for medical help immediately. Drink plenty of water and provide fresh air. Call for a doctor immediately.

 \cdot 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 3)

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 4)

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Provide floor trough without outlet.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2

· Hand protection





Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 5)

· Material of gloves


Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



· Body protection: Impervious protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Grey

· Odour: Characteristic · Odour threshold: Not determined. Undetermined.

· Melting point/freezing point:

· Boiling point or initial boiling point and boiling

137 °C (CAS: 1330-20-7 xylene) range

· Flammability Not applicable. · Lower and upper explosion limit

· Lower: 0.7 Vol % (CAS: 64742-95-6 Solvent naphtha

(petroleum), light arom.)

· Upper: 7.5 Vol % (CAS: 64742-95-6 Solvent naphtha

(petroleum), light arom.)

· Flash point: Not applicable.

450 °C (CAS: 64742-95-6 Solvent naphtha · Auto-ignition temperature:

(petroleum), light arom.)

· Decomposition temperature: Not determined.

Hα· Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. Not determined.

Vapour pressure:

Density and/or relative density

· Density at 20 °C: 2.27 g/cm³ · Relative density Not determined. · Vapour density Not determined.

(Contd. on page 7)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 6)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

• VOC (EC) % 14.00 % • VOC (EC) g/l 339.8 g/l

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 7)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4h	>10.2 ppm (rat)
CAS: 1330-20-7 xylene		
Dermal	LD50	1,100 mg/kg (rabbit)
Inhalative	LC50/4h	11 mg/m³ (rat)
CAS: 1314-13-2 zinc oxide		
Oral	LD50	>5,000 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 8)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Very toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods:
- · European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

· IMDG

- ADR UN1993 FLAMMABLE LIQUID, N.O.S. (Solvent

naphtha (petroleum), light arom., XYLENES),

ENVIRONMENTALLY HAZARDOUS

PAINT (zinc powder -zinc dust (stabilized), Solvent

naphtha (petroleum), light arom.), MARINE

POLLUTANT

· IATA PAINT

(Contd. on page 10)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

· Label

· IMDG





· Class 3 Flammable liquids.

· Label 3

·IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

• **14.5 Environmental hazards:** Product contains environmentally hazardous

substances: zinc powder -zinc dust (stabilized)

· Marine pollutant: Ye

Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

• EMS Number: F-E,S-E

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)5LCode: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category 3 · Tunnel restriction code D/E

(Contd. on page 11)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

5L

Trade name: Zinc dust paint E-COLL

(Contd. of page 10)

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN1993, FLAMMABLE LIQUID, N.O.S. (Solvent

naphtha (petroleum), light arom., XYLENES), ENVIRONMENTALLY HAZARDOUS, 3, III

SECTION 15: Regulatory information

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom. quicklime

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment

Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

(Contd. on page 12)



Printing date 07.10.2024 Version number 308 (replaces version 307) Revision: 07.10.2024

Trade name: Zinc dust paint E-COLL

(Contd. of page 11)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Product safety department

 Contact: Head of Product Safety Department · Date of previous version: 23.07.2024

· Version number of previous version: 307

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

· * Data compared to the previous version altered.